

Apache httpd configuratie

Settings /etc/httpd/conf/httpd.conf	Settings /etc/httpd/conf.d/clearos.default.conf of custom-httpd.conf	Settings /etc/httpd/conf.d/piwigo.conf
<pre>- ServerRoot "/etc/httpd" - Listen 80 - Include conf.modules.d/*.conf - User apache Group apache - ServerAdmin root@localhost - ServerName testserver.lan - <Directory /> AllowOverride none Require all denied </Directory> - DocumentRoot "/var/www/html" - <Directory "/var/www"> AllowOverride None # Allow open access Require all granted </Directory> - <Directory "/var/www/html"> #Options Indexes FollowSymLinks #AllowOverride None Require all granted </Directory> - <IfModule dir_module> DirectoryIndex index.html </IfModule> - <Files ".ht*"> Require all denied </Files> - AddDefaultCharset UTF-8 - IncludeOptional conf.d/*.conf</pre>	<pre>- # Authentication mechanism DefineExternalAuth pwauth pipe /usr/bin/pwauth DefineExternalGroup pwauth pipe /usr/bin/unixgroup - <VirtualHost *:80> ServerName makkink.eu ServerAlias *.makkink.eu DocumentRoot /var/www/html ErrorLog /var/log/httpd/error_log CustomLog /var/log/httpd/access_log combined CustomLog /var/log/httpd/wandelen_access_log combined env=wandelen CustomLog /var/log/httpd/nbp_access_log combined env=nbp CustomLog /var/log/httpd/blog_access_log combined env=blog </VirtualHost> - <Directory /var/www/html> Options -Indexes +FollowSymLinks -IncludesNOExec <FilesMatch \.php\$> SetHandler "proxy:fcgi://127.0.0.1:9073" </FilesMatch> Require all granted </Directory> - <VirtualHost *:443> ServerName makkink.eu ServerAlias *.makkink.eu DocumentRoot /var/www/html ErrorLog /var/log/httpd/error_log CustomLog /var/log/httpd/access_log combined CustomLog /var/log/httpd/wandelen_access_log combined env=wandelen CustomLog /var/log/httpd/nbp_access_log combined env=nbp CustomLog /var/log/httpd/blog_access_log combined env=blog SSLEngine on # SSL ClearOS self-signed certificaat-bestandslocaties SSLCertificateFile /etc/pki/CA/sys-0-cert.pem SSLCertificateKeyFile /etc/pki/CA/private/sys-0-key.pem SSLCACertificateFile /etc/pki/CA/ca-cert.pem # No weak export crypto allowed SSLHonorCipherOrder on SSLProtocol all -SSLv2 -SSLv3 -TLSv1 -TLSv1.1 SSLCipherSuite ECDHE-ECDSA...etc...:3DES:!aNULL:!MD5 SetEnvIf User-Agent ".MSIE.*" nokeepalive ssl-unclean-shutdown downgrade-1.0 force-response-1.0 </VirtualHost> - # Access_Logs: Zet 'env' voor paden 'wandelen', 'nbp' en 'blog' vanuit # de webroot en geef deze env's een alias (wandelen, nbp en blog) SetEnvIf Request_URI "/wandelen/" wandelen CustomLog logs/wandelen_access_log combined env=wandelen SetEnvIf Request_URI "/nbp/" nbp CustomLog logs/nbp_access_log combined env=nbp SetEnvIf Request_URI "/blog/" blog CustomLog logs/blog_access_log combined env=blog</pre>	<pre>- # Het e-mail adres waar de server naar toe mailt ServerAdmin ben@makkink.eu - # DirectoryIndex: het bestand dat Apache opent als een dir # wordt gevraagd (is in httpd.conf alleen index.html) <IfModule dir_module> DirectoryIndex index.html index.htm </IfModule> - # Indexering (listing) van bestanden toestaan in download dir <Directory "/var/www/html/exploringlinux/download"> Options +Indexes </Directory> - # Map naar bestanden buiten webroot met een alias en opties # Geef toegang voor alleen de hosts op het LAN Alias /manuals "/usr/share/doc" <Directory "/usr/share/doc"> Options Indexes AllowOverride None Require ip 192.168.1.0/24 # Require all granted </Directory> - # Forceer domein www.makkink.eu naar HTTPS <Directory /var/www/html> RewriteEngine On RewriteCond %{SERVER_PORT} 80 RewriteRule ^(.*)\$ https://www.makkink.eu/\$1 [R,L] </Directory></pre>
	<pre>Settings /etc/httpd/conf.d/errordocs.conf # ErrorDocuments directives multilinguale HTTP foutmeldingen - # Gebruik Alias /error/ voor path van de ErrorDocumenten Alias /error/ "/usr/share/httpd/error/" - # Benodigde permissies en instellingen voor weergave <IfModule mod_negotiation.c> <IfModule mod_include.c> <Directory "/usr/share/httpd/error"> AllowOverride None Options IncludesNoExec AddOutputFilter Includes html AddHandler type-map var Require all granted LanguagePriority nl en es de fr ForceLanguagePriority Prefer Fallback </Directory> ErrorDocument 401 /error/HTTP_UNAUTHORIZED.html.var ErrorDocument 403 /error/HTTP_FORBIDDEN.html.var ErrorDocument 404 /error/HTTP_NOT_FOUND.html.var </IfModule></pre>	<pre># PIWIGO beveiliging ../pwigo/galleries ipv .htaccess - <Directory /var/www/html/piwigo/galleries> Require all denied </Directory> - <Directory /var/www/html/piwigo/_data/i> <Files *-la.JPG> # Require all denied </Files> <Files *-xs.JPG> # Require all denied </Files> </Directory> # Voor blokkeren familiewebsite /var/www/html/archief # en toegang middels Piwigo Cookie - <Directory "/var/www/html/archief"> Require all denied SetEnvIf COOKIE ^GALLERYSID user_logged_in Require env user_logged_in </Directory> # Voor Piwigo beveiliging mbv .htaccess # In httpd.conf is AllowOverride naar None gezet # Indien gewenst hier toestaan voor Piwigo - <Directory /var/www/html/piwigo> # AllowOverride FileInfo Options AuthConfig Limit </Directory></pre>
		<pre>HTTP directives geplaatst door Apps /etc/httpd/conf.d/autaindex.conf weergave van icons bij dir listings door server /etc/httpd/conf.d/awstats.conf Awstats App /etc/httpd/conf.d/BackupPC.conf BackupPC App HttpAuth /etc/httpd/conf.d/php.conf PHP toevoeging autostart index.php /etc/httpd/conf.d/ssl.conf SSL virtual host 443 /etc/httpd/conf.d/userdir.conf Apache option, disabled bij default</pre>